

PLASTIC STRAPPING TOOLS **B SERIES**

B400 BATTERY POWERED FRICTION WELD TOOL



INCLUDES 2 BATTERIES

SPECIFICATIONS	
L x W x H	11.4" x 5.5" x 6.5"
WEIGHT	7.9 lbs.
BATTERY	14.8V-2 A/H LI-PO
MAX. TENSION	450 lbs.
TENSION SPEED	5.9 in/sec
SEALING/JOINT STRENGTH	Friction / 80% of Breaking
RECOMMENDED STRAP SIZE/THICKNESS	3/8", 7/16", 1/2", 5/8" polypropylene or polyester / .019" - .030"

B800 BATTERY POWERED FRICTION WELD TOOL



INCLUDES 2 BATTERIES

SPECIFICATIONS	
L x W x H	11.4" x 5.5" x 6.5"
WEIGHT	8.4 lbs.
BATTERY	14.8V-3 A/H LI-PO
MAX. TENSION	850 lbs.
TENSION SPEED	5.9 in/sec
SEALING/JOINT STRENGTH	Friction / 80% of Breaking
RECOMMENDED STRAP SIZE/THICKNESS	5/8" - 3/4" polypropylene or polyester / .025" - .040"

B1000 BATTERY POWERED FRICTION WELD TOOL



INCLUDES 2 BATTERIES

SPECIFICATIONS	
L x W x H	12.4" x 5.5" x 7.2"
WEIGHT	8.4 lbs.
BATTERY	14.8V-3 A/H LI-PO
MAX. TENSION	1125 lbs.
TENSION SPEED	5.9 in/sec
SEALING/JOINT STRENGTH	Friction / 80% of Breaking
RECOMMENDED STRAP SIZE/THICKNESS	5/8" - 3/4" polypropylene or polyester / .035" - .050"

B 400-1000 SERIES ACCESSORIES



BATTERY CHARGER
PRODUCT CODE
400CHG*
POWER SUPPLY
60 Hz 80W
OUTPUT
16V 5A

* Charges B400, B800 and B1000 Batteries

OPTIONAL
SUSPENSION
BRACKET



Product Code: 190144
FOR TOOL COUNTERBALANCER
SEE PAGE 14



BATTERIES	
PRODUCT CODE	
B400BAT	B800BAT*
TYPE	
LITHIUM	LITHIUM
OUTPUT	
14.8V 2AH	14.8V 3AH

*Also used for B1000 tool

CHARGE TIME IS JUST 20 MINUTES & THE BATTERY PROVIDES FOR APPROXIMATELY 200 CYCLES & A LIFE OF UP TO 2,000 CHARGES.