



"Speed, Flexibility, Dependable Performance"

T822CS
T822CM
T822CL

"Insight" Radiant Convection Tunnels



MADE IN U.S.A

Distributed by:



TEXWRAP®

525 Vossbrink Drive · Washington, MO 63090
Ph (636)239-7424 · Fax (636) 239-7322
sales@texwrap.com · www.texwrap.com

Features, Functions & Benefits

- Robust AC inverter duty motors
- Easy to read L.E.D. display(heat control)
- Infinitely adjustable fan speed
- Energy efficient heater design
- Lighted full length viewing window
- Easily accessible internal components(heaters)
- Heavy duty construction
- Durable powder coat finish
- Various belt options available
- Automatic cool down
- Adjustable height legs
- 150 feet per minute belt speed
- Belt direction field changeable
- Independently controlled zones, heat & airflow.

Specifications:	T822CS	T822CM	T822CL
Chamber Opening:	8”H x 22”W	8”H x 22”W	8”H x 22”W
Chamber Length:	60”L	84”L	120”L
Electrical:	230V, 30 amp, 3 phase	230V, 50 amp, 3 phase	230V, 60 amp, 3 phase
Conveyor Height:	Adj. from 30” to 36”	Adj. from 30” to 36”	Adj. from 30” to 36”
Conveyor Speed:	0 - 100 FPM	0 - 150 FPM	0 - 200 FPM
Conveyor Width:	20”	20”	20”
Footprint:	84”L x 43”W x 66”H	103”L x 43”W x 66”H	144”L x 43”W x 66”H
Shipping Weight:	750 lbs.	900 lbs.	1,400 lbs.

	T822CS	T822CM	T822CL
A=	60”	84.25”	120.25”
B=	24.25”	24.25”	24.25”
C=	84”	103”	144”
D=	Allow 72”	Allow 72”	Allow 72”
E=	30-36”	30-36”	30-36”
F=	43”	43”	43”

