



STANDARD MACHINE SPECIFICATIONS:

<u>Height Capability:</u>	<i>Minimum</i>	<i>Maximum</i>
Standard Model	30"	114"
<u>Width Capability:</u>	30"	60"
<u>Strapping Requirements:</u>	3/8" or 7/16" Polyester	
<u>Pallet Void Feeder Attachment:</u>	2-1/8" minimum void height with 3/4" bottom deck board	
<u>Conveyor Height:</u>	12"	
<u>Controls:</u>	Allen Bradley MicroLogix PLC Controlled	
<u>Electrical:</u>	230 or 460 Volt AC, 3 Phase, 60 Hz (Specify at time of order) 6.25 Amps @ 230 Volts, 3.2 Amps @ 460 Volts	
<u>Pneumatic Supply:</u>	1.1cu. ft. free air @ 80 PSI/cycle	
<u>Dispenser:</u>	Free Standing Non-Powered Model DF1-12D	
<u>Indexing Head Travel:</u>	Maximum Head Travel 20"	
<u>Optional Compression:</u>	Adjustable from 200 to 1,000 lbs.	

MACHINE PRICING

MCD-510-BCU RECONDITIONED (W/O COMPRESSION).....	\$29,995.00 EA
COMPRESSION	\$9,995.00 EA