



USED LOVESHAW MODEL LD-16SBX

MACHINE SPECIFICATIONS

MACHINE DIMENSIONS:	<p>HEIGHT: 70" 1778 mm</p> <p>WIDTH: 35" 890 mm</p> <p>LENGTH: 77" 1956 mm</p>
INFEED HEIGHT:	22 ¼" 565 mm STANDARD -
ELECTRICAL:	STANDARD: 115V/220V - 1 PH - 60 CYCLES
BOX CAPACITY:	<p>LENGTH: 8 ¼" min. to 24" max. 206 mm to 610 mm</p> <p>WIDTH: 4 ½" min. to 20" max. 114 mm to 508 mm</p> <p>HEIGHT: 4 ½" min. to 20" max. 114 mm to 508 mm</p>
OPERATING SPEED:	BELT SPEED: 60 ft/min 32.6 m/min.
NUMBER OF BOXES PER MIN.:	up to 14 depending on box dimension
CLOSURE MATERIAL:	PRESSURE SENSITIVE TAPE
WIDTH:	1 ½" to 2" 38 mm to 50 mm
MAX. ROLL DIAMETER:	15" 380 mm
WEIGHT:	(UNCRATED) 650 lbs. 302 kg.
AIR REQUIREMENTS:	0.15 cf. free air per cycle at 75 psi 4.2 liter free air at 5.3 kg per sq. cm.

DISCLAIMER: THE MACHINE SPECIFICATIONS LISTED ABOVE ARE FOR STANDARD LD16A TAPING MACHINES. THE SPECIFICATIONS OF THE INDIVIDUAL MACHINES WILL CHANGE DEPENDING ON EACH INDIVIDUAL CUSTOMER APPLICATION THE MACHINE WAS ORIGINALLY ORDER FOR.

UNIT PRICING

USED LOVESHAW LD16SBX PRICE \$6,500.00