

Chart of types model A480

Item No.	Model	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi				Max. Tension		Tension speed	
		Width		Thicknesses		N	lbs	mm/sec.	inch/sec.
		mm	inch	mm	inch				
13.4050	A480/10/0.38-0.63/4.5	10.0	3/8"	0.38-0.63	.015-.025	4500	1000	100	4.0
13.4052	A480/10/0.38-0.63/2.5	10.0	3/8"	0.38-0.63	.015-.025	2500	560	180	7.1
13.4070	A480/13/0.38-0.63/4.5	13.0	1/2"	0.38-0.63	.015-.025	4500	1000	100	4.0
13.4072	A480/13/0.38-0.63/2.5	13.0	1/2"	0.38-0.63	.015-.025	2500	560	180	7.1
13.4090	A480/16/0.38-0.63/4.5	16.0	5/8"	0.38-0.63	.015-.025	4500	1000	100	4.0
13.4092	A480/16/0.38-0.63/2.5	16.0	5/8"	0.38-0.63	.015-.025	2500	560	180	7.1
13.4110	A480/19/0.38-0.63/4.5	19.0	3/4"	0.38-0.63	.015-.025	4500	1000	100	4.0
13.4112	A480/19/0.38-0.63/2.5	19.0	3/4"	0.38-0.63	.015-.025	2500	560	180	7.1

Uniflex = Regular duty strapping max. 850 N/mm² / 123'000 psi
 Ultraflex = High tensile strapping max. 1100 N/mm² / 160'000 psi

Accessories

A48.1304 Suspension bracket for
horizontal and vertical applications

Recommended seals

Width mm	Inch	Dimensions (W, L, T)	
		mm	inch
10	3/8"	10 x 22 x 0.6	³ / ₈ x ⁷ / ₈ x .024
13	1/2"	13 x 22 x 0.6	¹ / ₂ x ⁷ / ₈ x .024
16	5/8"	16 x 22 x 0.6	⁵ / ₈ x ⁷ / ₈ x .024
19	3/4"	19 x 22 x 0.6	³ / ₄ x ⁷ / ₈ x .024

Tensile strength of the seal material: 600 N/mm² / 87'000 psi