

Plastic strapping machine

Jam-resistant technology Automatic strap feed

Up to **70** straps per minute!





Made in the U.S.A.



Signode's new LBX-2000[™] offers the most reliable performance, lowest maintenance cost and highest speed of any general duty strapping machine on the market today.

- Up to 70 straps per minute
- Jam-resistant technology
- Automatic refeed
- Lubrication-free
- No internal adjustments necessary

Easy coil loading

Strap coil pays off from either direction making loading simpler than ever.



Fully accessible strap path

Raise the hinged tabletop to open the chute. Lift guide for full access to strap path.





Easy maintenance

No belts or clutches. Hot knife can be removed and cleaned without the use of any tools.





3610 West Lake Avenue Glenview, Illinois 60025 1-800-323-2464

Save up to 20% on material costs with LB Series plastic strapping

The new LBX-2000 utilizes Signode's newest Contrax[®] polypropylene strapping. LB Series strapping has the same durable properties as regular Contrax with more strap per coil.


- LB 112 5mm Contrax coils 30,000 feet per coil
- LB 212 6mm Contrax coils 24,000 feet per coil

LBX-2000 Specifications

Cycle rate: Up to 70 straps per minute Strap size: 5mm or 6mm wide polypropylene strapping Strap tension: Adjustable from 2 lbs to 60 lbs Machine dimensions: 31" W x 21" L x 57" H (790mm W x 530mm L x 1450mm H), maximum height Tabletop height: 34" (865mm) Electrical requirements: 110 volt, 60Hz Shipping weight: 540 lbs

Chute inner dimensions:

	Small chute		Large chute	
	inches	mm	inches	mm
Α	20	510	28	710
В	15	380	15	380



Options

- 3-stage electric photo eye
- Remote cycle switch