

T1322
T822M
T1432

Single Tunnels



MADE IN U.S.A

Distributed by:

Features, Functions & Benefits

- Continuous duty industrial grade blower motor
- Easy to read L.E.D. display
- Cool-Touch energy efficient design
- DC motor with variable speed control for conveyor speed
- Top air velocity control for the adjustment of air flow to the top or bottom of the package for even shrink
- Audible high heat alarm and high heat limit thermostat
- Stainless steel mesh belt
- Durable powder coat finish
- Various belt options available
- Automatic cool down

MODEL	T-1322	T-822M	T-1432
OPENING	13"H x 22"W	8"H x 22"W	14"H x 32"H
ELECTRICAL	230V/ 3phase / 36 amps	230V/ 3 phase/ 34 amps	230V/ 3phase / 50 amps
HEATERS	3 flange cal-rod types	3 flange cal-rod types	3 flange cal-rod types
CONVEYOR HEIGHT	adj. 30" - 35"H	adj. 30" - 35"H	adj. 30" - 35"H
CONVEYOR SPEED	0- 100 FPM	0- 150FPM	0- 150 FPM
MACHINE DIMENSIONS	58"L x 45"W x 74-79"H	112"L x 46"W x 74-79"H	103.5"L x 55"W x 74-79"H
SHIPPING WEIGHT	826 lbs.	1150 lbs.	1050 lbs.
CONVEYOR WIDTH	15"	15"	24"
CHAMBER LENGTH	42 -1/4"	64"	55"

	T-1322	T-822M	T-1432
A=	3' 6 1/4"	5' 4"	4' 7"
B=	2' -10 3/4"	2'-10 5/8"	3' - 8 1/2"
C=	4' -10"	9' 4"	8' -7 3/8 "
D=	6' 2"	6' 2"	6' 7"
E=	2' 6"	2'-6"	2' 6"
F=	3' - 10"	3'-10"	4' - 8"

